GM Mini Conical Abutment

Multiple-unit screw-retained prosthesis

Ø 4.8 mm

Check it out on the eShop, go to: neodent.com/shopnow

Consider in addition 1.5 - 2.0 mm for the restorative material;

Minimum interocclusal space of 4.5 mm from the mucosa level for straight abutments;

Exact;

Neo Removable Screw.



Installation Sequence



32 N.cm (1) GM Mini Conical Abutment

0.8 mm	1.5 mm	2.5 mm
115.243	115.244	115.245
3.5 mm	4.5 mm	5.5 mm
115.246	115.247	115.248

or



20 N.cm (2) GM Exact Mini Conical Abutment 17°/30°

	1.5 mm	2.5 mm	3.5 mm
17°	115.275	115.276	115.277
30°	115.278	115.279	115.280

Intraoral



Mini Conical Abutment Scanbody (3) 108.218



Mini Conical Abutment Hybrid Repositionable Analog 101.092

or



Neo Mini Conical Abutment One Step Hybrid Coping

10 N.cm (2)

118.382 Regular

118.410 Long



Neodent DirectFit Screw

20 N.cm (2)

116.303

Model Scanning



Slim Mini Conical Abutment Open Tray Impression Coping (3) 108.176



Mini Conical Abutment Hybrid Repositionable Analog 101.092



Mini Conical Abutment Scanbody (3) 108.218

or



Neo Mini Conical Abutment One Step Hybrid Coping

10 N.cm (2)

118.382 Regular

118.410 Long



Neodent DirectFit Screw

20 N.cm (2)

116.303

Conventional



Slim Mini Conical Abutment Open Tray Impression Coping (3) 108.176



Neo Mini Conical Abutment Titanium Coping

10 N.cm (2)

118.302

or



Neo Mini Conical Abutment Protection Cylinder (3)

106.268 Regular

106.278 Wide



Mini Conical Abutment Analog

101.092 Hybrid Repositionable (conventional/digital)

101.020 Conventional (1 un.)

101.112 Conventional (5 un.) NEW ITEM



Neo Mini Conical Abutment CoCr Coping

10 N.cm (2)

118.303

or



Neo Mini Conical Abutment Burn-out Coping

10 N.cm (2)

118.301

Drivers

1  Hexagonal Prosthetic Driver +  Torque Wrench

2  Neo Screwdriver Torque Connection +  Torque Wrench

3  Neo Screwdriver Torque Connection +  Manual Screwdriver Torque

Accessories



Replacement Abutment Screw

116.291 Neo GM Screw - for abutments with 1.5-2.5 GH

116.292 Neo GM Screw (Long) - for abutments with 3.5 GH



Sealing pin mini conical abutment one step hyb cop (5 un.)

118.411



Mini Conical Abutment Polishing Protector

123.008



Replacement Coping Screw

116.269 Titanium

116.270 Neotorque*

*Application of a film carbon-based coat that provides a lower friction coefficient, resulting in increased pre-load.